

AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP – Rev. 00

Date 06/05/13

Page 1 of 4

1.	Univocal	product-ty	ype identification	code: CLASS	SIC-AL BATH	(com	plete rang	ge)
----	----------	------------	--------------------	-------------	-------------	------	------------	-----

- 2. Type, lot, series no. or any other element that enables the construction product to be identified pursuant to article 11, paragraph 4: **CLASSIC-AL BATH**
- 3. Intended use(s) of the construction product according to the relative harmonised technical specification, as stated by the manufacturer: Heat emitting radiators designed for permanent installation in heating systems of residential buildings, fed from a remote source with hot water or steam at a temperature < 120 °C. (EN 442-1 December 2014, EN 442-2 December 2014)
- 4. Name, registered trade name or registered trademark and address of the manufacturer pursuant to article 11, paragraph 5: Radiatori 2000 S.p.a. Via Francesca, 54/A 60 24040 Ciserano (BG) ITALY
- 5. If applicable, name and address of mandatary whose mandate includes the assignments as per article 12, paragraph 2: **N.A.**
- 6. System(s) for the assessment and verification of constancy of performance of the construction product, as per annex V: **system 3**.
- 7. In a declaration of performance concerning a construction product that comes under the scope of a harmonised standard:

Notified Testing Laboratory: Politecnico di Milano – Energy Department (Notified body number: 1695)

(name and identification number of notified body, if applicable)

has performed **type tests (standard UNI EN 442-1)** according to system **3.** (description of third party assignments as per annex V)

and has issued:

- Determination of the thermal output of a heating body (Test report ENE/MRT.ITPL-14005 of 24/02/14)
- Pressure tightness tests (Test report ENE/MRT.ITPL.14005 of 24/02/14) (constancy of performance certificate, plant production control conformity certificate, test/design reports as applicable)

(name and identification number of organisation notified, if applicable)
(description of third party assignments as per annex V)
and has issued:
(constancy of performance certificate, plant production control conformity certificate, test/design reports – as applicable)



AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP – Rev. 00

Date 06/05/13

Page 2 of 4

8. In a declaration of performance concerning a construction product for which a European technical assessment has been released:

N.A. (name and identification number of technical assessment body, if applicable)
has released
(reference number of European technical assessment)
based on
(reference number of European assessment document)
performed
and has issued
(constancy of performance certificate, plant production control conformity certificate, test/design reports – as applicable)

9. Performance declared

Notes to table:

- 1. Column 1 contains the list of the basic properties as defined in the harmonised technical specifications for the use(s) specified in § 3 above;
- 2. For each property listed in column 1 and conforming to the requirements as per article 6, this column gives the performance declared, expressed in terms of level, class, or through a description, in relation to the corresponding basic properties. If no performance has been declared, the column shows "NPD" (No Performance Determined):
- 3. For each basic property listed in column 1, column 3 gives:
 - A reference, with relative date, to the corresponding harmonised standard, and, if applicable, the reference number of the specific technical documentation, or that of the appropriate technical documentation used:

or

b. A reference, with relative date, to the corresponding European assessment document, if available, and the reference number of the European technical assessment used;



AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP – Rev. 00

Date 06/05/13

Page 3 of 4

Basic properties (see note 1)	Performance (see note 2)	Harmonised technical spec. (see note 3)
Reaction to fire	A1	Tests on organic part of any paint or surface treatment substance to verify whether it is <1 % by mass. (Clause 5.2, standard EN 442-1:2014)
Release of hazardous substances	None	Clause 5.3, standard EN 442- 1:2014
Surface temperature	120° C maximum and corresponding to water supply temperature	EN 442-1:2014
Maximum operating pressure	16 bar	EN 442-1:2014
Pressure tightness (leak test)	20,8 bar	Clause 5.4, standard EN 442- 1:2014
Pressure tightness (resistance test)	27 bar	Clause 5.6, standard EN 442- 1:2014
Rated thermal output ΔT 50 K	See Table 1	Clause 5.8, standard EN 442- 1:2014
Rated thermal output ΔT 30 K	See Table 1	Clause 5.8, standard EN 442- 1:2014
Thermal power in different operating conditions (Characteristic equation)	$\Phi = Km \times \Delta T^n$	Clause 5.8, standard EN 442- 1:2014
Coefficient Km	See Table 1	Clause 5.8, standard EN 442- 1:2014
Coefficient n	See Table 1	Clause 5.8, standard EN 442- 1:2014
Durability (impact resistance lightweight)	Level 0	Clause 5.9, standard EN 442- 1:2014
Durability (corrosion test)	No corrosions after 100 h of humidity	Clause 5.9, standard EN 442- 1:2014

If a specific techni product:	ical document	has been used	d, pursuant to a	rt. 37 or art. 38	, the requireme	nts met by the	

10. The performance of the product as per §§ 1 & 2 above conforms to the performance declared as per § 9.



AS PER ARTS. 4, 6, 7 AND ANNEX III TO REG. (UE) 9-3-2011, No. 305/2011

MOD.CL.DDP – Rev. 00

Date 06/05/13

Page 4 of 4

TABLE 1 (tecnica data)

Modell	Rated thermal output ΔT 50 K	Rated thermal output ΔT 30 K	Coefficient Km	Coefficient n
Classic-Al Bath (80/40)	319,0 Watt	169,4 Watt	2,515	1,238
Classic-Al Bath (80/45)	349,0 Watt	185,5 Watt	2,762	1,237
Classic-Al Bath (80/50)	380,0 Watt	202,1 Watt	3,011	1,236
Classic-Al Bath (80/55)	410,0 Watt	218,1 Watt	3,261	1,235
Classic-Al Bath (80/60)	440,0 Watt	234,2 Watt	3,514	1,234
Classic-Al Bath (120/40)	471,0 Watt	250,6 Watt	3,745	1,235
Classic-Al Bath (120/45)	518,0 Watt	276,3 Watt	4,208	1,230
Classic-Al Bath (120/50)	564,0 Watt	301,8 Watt	4,690	1,224
Classic-Al Bath (120/55)	611,0 Watt	327,9 Watt	5,191	1,218
Classic-Al Bath (120/60)	657,0 Watt	353,7 Watt	5,713	1,212
Classic-Al Bath (150/40)	571,0 Watt	305,2 Watt	4,704	1,226
Classic-Al Bath (150/45)	627,0 Watt	335,6 Watt	5,227	1,223
Classic-Al Bath (150/50)	682,0 Watt	365,7 Watt	5,763	1,220
Classic-Al Bath (150/55)	738,0 Watt	396,3 Watt	6,312	1,217
Classic-Al Bath (150/60)	794,0 Watt	427,2 Watt	6,873	1,213
Classic-Al Bath (180/40)	687,0 Watt	369,1 Watt	5,894	1,216
Classic-Al Bath (180/45)	751,0 Watt	403,7 Watt	6,454	1,215
Classic-Al Bath (180/50)	815,0 Watt	438,1 Watt	7,015	1,215
Classic-Al Bath (180/55)	879,0 Watt	472,5 Watt	7,578	1,215
Classic-Al Bath (180/60)	944,0 Watt	507,7 Watt	8,141	1,214

This declaration of performance is released under the sole responsibility of the manufacturer as per § 4 above.

Signed in the name and on behalf of:

ARIANNA SCARAVAGGI

Managing Director (name and functions)

(signature)